N68PV-GS

- Support for Socket AM2+ / AM2 processors: AMD Phenom™ FX / Phenom / Athlon 64 FX / Athlon 64 X2 Dual-Core / Athlon X2 Dual-Core / Athlon 64 / Sempron processor
- NVIDIA® GeForce 7050 / nForce 630A MCP Chipset
- AM3 CPU Ready!
  - FSB 1000 MHz (2.0 GT/s)
  - Supports Dual Channel DDR2 1066 with AM2+ CPU, and DDR2 800/667/533 with AM2 CPU, 2 x DIMM slots, maximum capacity up to 8GB
  - ASRock AM2 Boost: ASRock Patented Technology to boost memory performance up to 12.5%
  - Integrated NVIDIA® GeForce7 Series (NV44) DX9.0 VGA, Pixel Shader 3.0, Max. shared memory 256MB
  - 1 x PCI Express x16 slot
  - Dual VGA Output: Support DVI-D and D-Sub ports by independent display controllers
  - Supports HDCP function with DVI-D port, to enjoy better quality with High Definition HDCP Encryption contents
  - Supports Full HD 1080p Blu-ray (BD) / HD-DVD playback
  - NVIDIA® PureVideo™ Ready
  - 4 x SATAII 3.0 Gb/s, support RAID (RAID 0, RAID 1, RAID 0+1, RAID 5 and JBOD), NCQ, AHCI and "Hot Plug" functions
  - Gigabit LAN 10/100/1000 Mb/s
  - 5.1 CH Windows® Vista™ Premium Level HD Audio (ALC662 Audio Codec)
  - Chipset embedded HDMI Audio
  - Supports Instant Boot
  - Supports Smart BIOS, ASRock OC Tuner, Intelligent Energy Saver, Extra ESD Protection
  - I/O Panel: 1 x VGA/D-Sub Port, 1 x VGA/DVI-D Port, 1 x RJ-45 LAN Port with LED, 4 x Ready-to-Use USB 2.0 Ports

This model may not be sold worldwide. Please contact your local dealer for the availability of this model in your region.

Product Specifications

General	
CPU	- Support for Socket AM2+* / AM2 processors: AMD Phenom™ FX / Phenom / Athlon 64 FX / Athlon 64 X2 Dual-Core / Athlon X2 Dual-Core / Athlon 64 / Sempron processor - Supports AMD's Cool 'n' Quiet Technology - FSB 1000 MHz (2.0 GT/s) - Supports Untied Overclocking Technology - Supports Hyper-Transport Technology - AM3 CPU Ready *If you use AM3 / AM2+ CPU on AM2 chipset motherboard, the system bus speed will downgrade from HT3.0 (5200 MT/s) to HT1.0 (2000 MT/s), but the CPU frequency will not be influenced.
Chipset	- NVIDIA® GeForce 7050 / nForce 630A MCP
Memory	- Dual Channel DDR2 memory technology - 2 x DDR2 DIMM slots - Supports DDR2 1066*/800/667/533 non-ECC, un-buffered memory - Max. capacity of system memory: 8GB** *Support with AM2+ CPU. **Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® XP and Windows® Vista™. For Windows® XP 64-bit and Windows® Vista™ 64-bit with 64-bit CPU, there is no such limitation.
BIOS	- 4Mb AMI BIOS - AMI Legal BIOS - Supports "Plug and Play" - ACPI 1.1 Compliance Wake Up Events - Supports jumperfree - SMBIOS 2.3.1 Support - Supports Smart BIOS
Audio, Video and Networking	
Graphics	- Integrated NVIDIA® GeForce7 Series (NV44) - DX9.0 VGA, Pixel Shader 3.0 - Max. shared memory 256MB - Dual VGA Output: support DVI-D and D-Sub ports by independent display controllers - Supports HDCP function with DVI-D port - Supports Full HD 1080p Blu-ray (BD) / HD-DVD playback - NVIDIA® PureVideo™ Ready
Audio	- 5.1 CH Windows® Vista™ Premium Level HD Audio (ALC662 Audio Codec) - Chipset embedded HDMI Audio
LAN	- Gigabit LAN 10/100/1000 Mb/s - Giga PHY Realtek RTL8211CL - Supports Wake-On-LAN
Expansion / Connectivity	
Slots	- 1 x PCI Express x16 slot - 1 x PCI Express x1 slot - 2 x PCI slots
Connector	- 4 x SATAII 3.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 0+1, RAID 5 and JBOD), NCQ, AHCI and "Hot Plug" functions - 1 x ATA133 IDE connector (supports 2 x IDE devices) - 1 x Floppy connector - 1 x COM port header - 1 x Print port header

	- CPU/Chassis FAN connector - 24 pin ATX power connector - 4 pin 12V power connector - CD in header - Front panel audio connector - 2 x USB 2.0 headers (support 4 USB 2.0 ports)
Rear Panel I/O	I/O Panel - 1 x PS/2 Mouse Port - 1 x PS/2 Keyboard Port - 1 x VGA/D-Sub Port - 1 x VGA/DVI-D Port - 4 x Ready-to-Use USB 2.0 Ports - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - HD Audio Jack: Line in / Front Speaker / Microphone
Other Features / Miscellaneous	
Unique Feature	- ASRock OC Tuner - Intelligent Energy Saver - Instant Boot - Hybrid Booster: - CPU Frequency Stepless Control - ASRock U-COP - Boot Failure Guard (B.F.G.) - ASRock AM2 Boost: ASRock Patented Technology to boost memory performance up to 12.5%
Support CD	- Drivers, Utilities, AntiVirus Software (Trial Version)
Accessories	- Quick Installation Guide, Support CD, I/O Shield - ATA 133 Cables (optional) - 1 x SATA Data Cable (optional) - 1 x SATA 1 to 1 Power Cable (optional)
Hardware Monitor	- CPU Temperature Sensing - Chassis Temperature Sensing - CPU Fan Tachometer - Chassis Fan Tachometer - CPU Quiet Fan - Voltage Monitoring: +12V, +5V, +3.3V, Vcore
Form Factor	- Micro ATX Form Factor: 9.6-in x 7.2-in, 24.4 cm x 18.3 cm
OS	- Microsoft® Windows® 2000 / XP / XP 64-bit / Vista™ / Vista™ 64-bit compliant
Certifications	- FCC, CE, WHQL

Caution:
Please realize that there is a certain risk involved with overclocking, including adjusting the setting in the BIOS or using the third-party overclocking tools. Overclocking may affect your system stability, or even cause damage to the components and devices of your system. It should be done at your own risk and expense. We are not responsible for possible damage caused by overclocking.

The specification is subject to change without notice in advance. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

© 2002-2009 ASRock Inc. All rights reserved. | Information published on ASRock.com is subject to change without notice.